

DA-LP1101R / DA-LP1101T



Long Reach PoE Extender

- Up to 500meters PoE transmission between devices using UTP cabling
- Supports 1Gbps / IEEE802.3at for PoE Injector
- Up to 700meters DATA transmission between equipments using UTP cabling
- Supports 1Gbps / IEEE802.3at / 100meters for PoE Repeater
- Plug-and-play without any required PC setting

SPECIFICATIONS

PoE INJECTOR / REPEATER FUNCTION	
port	RJ45x1 with PD RJ45x1 with PSE
connectivity	RJ45 Auto-MDI/MDI-X Sensing
Power Input	IEEE802.3at, 48 ~ 56V DC
Power Output	Max. 720mA
PoE Standard	IEEE802.3at PD IEEE802.3at PSE
PSE Budget	up to 30W
Speed	10/100/1000Mbps
LONG REACH PoE EXTENDER FUNCTION	
port	RJ45x1 with PD RJ45x1 with PSE
connectivity	RJ45 Auto-MDI/MDI-X Sensing
Power Input	IEEE802.3at, 48 ~ 56V DC
Power Output	Max. 720mA
PoE Budget	Up to 30W(Depending on Cable Distance and Power Input)
cable	UTP CAT5Eor Above
Speed	10/100Mbps
LEDs and BUTTON	
Link Status LED	2 Yellow LED(Link/ Activity LEDper Ethernet port)
PoE Status	1 Green LED(PSELED)
Reset Button	None
Power LED	1 Green LED
GENERAL	
Dimensions (W x H x D)	104 x 34 x 96(mm)
Unit Weight	226g
Operating Temperature	-10°C ~ 50°C
Operating Humidity	0% ~ 90%
Power Input	56VDC
Power Consumption	56V=, 0.786A, 44W
Approvals	KC, CE, FCC



PRODUCT IMAGE



DIMENSIONS

