

DC-D4536RX

5MP IR Dome Camera



- Easy installation with DirectIP NVR
- micro SD/SDHC/SDXC, Smart Failover
- PoE (IEEE 802.3af Class 3), 12V DC
- IR LED (30m / 98.4 ft (6ea))
- 5MP (2592x1944) resolution
- Two-way audio
- Day and night (ICR)
- 3-axis mechanical design for installation
- Motorized Vari-focal lens (f=3.0 - 13.5mm)
- Alarm in / out
- True wide dynamic range (WDR)
- Supports ONVIF

SPECIFICATIONS

Video	
Image Sensor	1/2.8" CMOS
Max. Resolution	2592 x 1944
Scanning Mode	Progressive Scan
Lens Type	Motorized Vari-focal
Focal Length	3.0 ~ 13.5mm
Aperture	F1.4 ~ 3.2
Iris Control	DC Iris
Angular Field of View	[4:3 mode] Wide : 91°(H) 66°(V) 120°(D) Tele : 31°(H) 23°(V) 38°(D) [16:9 mode] Wide : 91°(H) 49°(V) 107°(D) Tele : 31°(H) 17°(V) 35°(D)
Min. Illumination	COLOR: 0.15 lux @ F1.4 B/W : 0 lux (IR LED ON)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	Yes (ICR)
IR Distance (LEDs)	30m / 98.4 ft (6ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode (Sharpness, Contrast, Colors, Brightness Control)
Backlight Compensation	BLC
Mirroring / Pivot	Horizontal / Vertical / Pivot
De-fog	Yes
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Pan/Tilt/Rotate	
Pan Range	-175° ~ 175°
Tilt Range	0° ~ 67°
Rotate Range	-177° ~ 177°
Network	
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Yes
Bitrate Control	H.265 - CBR/ VBR H.264 - CBR/ VBR
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S/T
Max. Frame Rate	4:3 mode : 30ips : 2592 x 1944(WDR) 16:9 mode : 30ips : 2592 x 1456(WDR)
Supported Resolution	4:3 : 2592x1944, 1920x1440, 1280x960, 640x480 16:9 : 2592x1456, 1920x1080, 1280x720, 640x360
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/RTCP/RTMTP/RTSP/HTTP/HTTPS/TCP/UDP/FTP/SFTP/HTTP/HTTPS/FTP/SNTP/SMTP/FEN/mDNS, uPNP, SNMPv2
Security	Digest authentication, Password Protection, User access log, IP Filtering, IEEE802.1X/802.1Q/802.1P, Chained Fingerprint, SSLEncryption, HTTPSEncryption
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTRec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Alarm and Event	
Trigger Event	Motion Detection, Alarm in, Audio detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with Image)
Audio Alarm	Yes
Audio In / Out	1(Built In MIC)+1 / 1
Alarm In / Out	1 / 1
Environmental	
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	12VDC, PoE, IEEE802.3af(Class3)
Power Consumption	12V~, 1A, 12W PoE IEEE802.3af(Class3), 9.5W
Approval	FCC, CE, KC
Mechanical	
Dimensions	Ø122.4 x 103.4mm (Ø4.82" x 4.07")
Weight	0.4kg (0.88lb)



PRODUCT IMAGE



DIMENSIONS













Unit - mm (inch)



ACCESSORIES (OPTIONAL)



ACCESSORY CONFIGURATION BY INSTALLATION ENVIRONMENT

PRODUCT	INSTALLATION ENVIRONMENT	ACCESSORY CONFIGURATION	
DC-D4536RX	WALL	 MOUNT ADAPTER Model:DA-MA4300	
		+	
		 WALL MOUNT Model:DA-WM2050	
		or	
	CELLING	 MOUNT ADAPTER Model: DA-MA4300	
		+	
		 CEILING MOUNT Model: DA-CM2050	
		POLE	 MOUNT ADAPTER Model: DA-MA4300
	+		
	 WALL MOUNT Model: DA-WM2050		
	+		
	POLE	 POLE MOUNT Model: DA-LM2000	
		CORNER	 MOUNT ADAPTER Model:DA-MA4300
			+
	 WALL MOUNT Model:DA-WM2050		
	CORNER	+	
 CORNER MOUNT Model:DA-RM2000			
ETC		 FLUSH MOUNT Model: DA-FM1500	
	or		
	 INDOOR DOME Model: DA-FM1600		