

DP-HE1201



- Ease integration with 3rd party system
- Supports HDMI and VGA input ports
- Supports Up to 3840 x 2160 resolution
- Remote Mouse and Keyboard Control through USB interface
- Quadruple Streaming



SPECIFICATIONS

ENCODER	
Video codec	H.265, H.264, MJPEG Intelligent Codec
Max. Framerate	3840 x 2160 @ 30ips
Bitrate	Up to 18MP
Max Resolution	3840 x 2160
Streaming	Quadruple Streaming
Max.Network Throughput	50Mbps
Input	1 x HDMI 1 x VGA
Output	1 x HDMI (Input Bypass) 1 x VGA (Input Bypass)
Audio Input / output	1 x line in (3.5mm) 1 x line out (3.5mm)
Serial Interface	1 x USB type B
Network interface	1 x RJ45 (10/100)
IP Camera Protocol	DirectIP 2.0, ONVIF
GENERAL	
Dimensions (W x H x D)	200mm x 44mm x 153mm (7.9" x 1.7" x 6.0")
Weight	0.8kg (1.76lb)
Operation Temperature	0°C ~ 40°C (32°F ~ 104°F)
PoE (Class)	Yes (IEEE 802.3af Class 3)
Power Source	12VDC, PoE (IEEE 802.3af Class 3)
Power Consumption	12V= 0.95A, 11.4W PoE, IEEE 802.3af(Class 3)
Approvals	FCC, CE, KC

DIMENSIONS

(Unit - mm)

